Mechanical Anch

The original self drilling plasterboard anchor, quick and easy to install using only a screwdriver.



Substrates

- Plasterboard dry partition walls
- Aerated concrete (with pre-drilled hole Ø 8mm)

Applications

- Bathroom accessories
- Fuse boxes
- Bracketry
- Signage
- Mirrors
- Dado rails
- Radiators (Driva® Plus only)
- Trunking (Mini Driva®)

ALSO AVAILABLE

Available in bag packaging:

Refer to page 181 for further details on the bag range











Features and Advantages

- High strength Zamak 3 body
- A range of fixings for different applications
- Positive tightening of the anchor
- No need for pre-drilling
- Corrosion resistant
- Point breaks away if an overlong screw has been used
- Removable
- · Head sits flush behind fixture
- Low profile head
- Screw thread profile designed for efficient cutting and ensures a positive lock
- No maximum or minimum plasterboard thickness (excluding Driva® Plus)
- Driva® Plus combines screw and clamp fixing
- Mini Driva® for fixing trunking to plasterboard

Installation - Driva®



Installation - Driva® Plus



Technical Specification

One piece self drilling anchor designed for fastening light / medium loads to plasterboard. For use in plasterboard, simply screw using a normal or power screwdriver. The point drills a pilot hole followed by a coarse, specifically designed helical thread biting into the plasterboard substrate making the fix. The separate screw is then used to mount the fixture.

When using standard Driva® in aerated concrete it is necessary to drill a 8mm diameter pilot hole.

Driva® Plus works in the same way as standard Driva® in plasterboard, but is designed for fixing heavier loads. The additional hinged toggle swivels and pulls towards the inner face of the cavity through the action of the mounting screw. This gives a combined screw and clamp fix.


Mini Driva® is used on its own, whereas other Driva® products require a screw to secure the fixture, and in the case of Driva® Plus, rotate the toggle.

Material - Anchor Body


Driva®, Driva® Plus, Mini Driva® -Zamak 3

Driva® LD - Glass Fibre Reinforced Nylon Polyamide

Installation - Mini Driva®



Installation - Driva® LD







Light Duty Anchor

Driva® Original Self Drilling Plasterboard Fixing

The fastest self drilling plasterboard fixing - Good pull-out values with efficient dust disposal. 100% Zamak.



| Eurocode | Description | Anchor Length | Screw Length | Drill Ø* | Max Fixture Thickness | Box Qty |
|---|----------------------|------------------|-----------------|-------------|--------------------------|------------|
| 059360 | Driva® TP12 | 31mm | 35mm | 8mm | 12mm | 100 |
| 059380 | Driva® TF27 | 31mm | 50mm | 8mm | 27mm | 100 |
| 059370 | Driva® TF5 | 31mm | 25mm | 8mm | 5mm | 100 |
| 059910 | Driva® F12 (Plastic) | 31mm | 35mm | - | 12mm | 100 |
| * For one drilling into constant concrete | | | | | | |

Mini Driva® One Step Self Drilling Plasterboard Fixing

Ideal for fixing mini trunking, skirting boards and beading - One step installation saves time, leaving a fine finish. 100% Zamak.



| Eurocode | Description | Anchor Length | Head Ø | Hole Ø | Max Fixture Thickness | Box Qty |
|----------|-------------|------------------|-----------|-----------|--------------------------|------------|
| 059430 | Mini Driva® | 25mm | 7.5mm | 5mm | 5mm | 200 |

Driva® Plus Self Drilling Plasterboard Fixing

Self drilling anchor for heavy loads - Clamp fix system enables high performance in plasterboard. 100% Zamak.



| Eurocode | Description | Anchor Length | Screw Length | Max Fixture Thickness | Box Qty |
|----------|-------------------|------------------|-----------------|--------------------------|------------|
| 061190 | Driva® Plus TP12* | 39mm | 45mm | 12mm | 100 |

^{*} TP = Pan Head ** TF = Countersunk

Driva® LD Self Drilling Non Conductive Plasterboard Fixing

Fast anchor for light loads - Constructed from a mix of nylon and fibreglass, for electrical installations.



| Eurocode | Description | Anchor Length | Screw Length | Max Fixture Thickness | Box Qty |
|----------|----------------|------------------|-----------------|--------------------------|------------|
| 058850 | Driva® LD TP12 | 30mm | 25mm | 12mm | 200 |

Driva® TP12 Kit with Screwdriver



| Eurocode | Description | Kit Qty |
|----------|---|------------|
| 074180 | Driva® TP12 200nc Kit, with Screwdriver | 200 |

