

BIS RapidRail® Connectors 90°


to make BIS RapidRail® fabrications




RAL-GZ 655/D
Cert.Nr. 2012-09

Features and benefits


- connector with pre-assembled BIS RapidRail® Slide nut(s)
- to make rail fabrications
- suitable for WM0, 1, 15, 2, 30, 35
- ready-to-use pre-assembled for a quick fixing, and retains assembly in place before final tightening
- material: metal parts made of steel 1.0332; spring(s) made of POM (polyoxymethylene), green
- zinc plated




658 4 001




658 4 002



658 4 003



658 4 011



Part No.	Model	For Rail	a (°)	T (Nm)	Fa,z (N)	Fa,x (N)	RAL	Pack 1
658 4 001	Long / long	WM0 - 35	90°	15	1.562	1.109	RAL ¹	25
658 4 002	Short / long	WM0 - 35	90°	15	1.336	448	RAL ¹	25
658 4 003	Short / short	WM0 - 35	90°	15	1.336	448	RAL ¹	25
658 4 011	Long / long	WM0 - 35	90°	15	1.562	1.109	RAL ¹	25

RAL¹ = tested, certified and externally monitored according to RAL-GZ 655/D in combination with Rail WM1, 2, 15 and 30.

For detailed technical information about our RAL marked products, please see the RAL datasheet in our webcatalogue: www.walraven.com/gb/en/catalogue/.

Complementary

BIS RapidRail® Fixing Rail